



Retinal Disease Classification Using Deep Learning and Nanotechnology with a Multi-class CNN Approach and Explainable AI

Kachi Anvesh^{1*}, E. Ravi Kumar¹, Subhav Singh², M. Babu Reddy³, Deekshant Varshney⁴ and Swetha Polisetty¹

¹Department of Information Technology, Vardhaman College of Engineering, Hyderabad, TG, India

²Chitkara Centre for Research and Development, Chitkara University, HP, India

³Department of Computer Science, Krishna University, Machilipatnam, AP, India

⁴Division of Research & Innovation, Uttarakhand University, Dehradun, UK, India

Received: 05.02.2026 Accepted: 27.02.2026 Published: 30.06.2026

*anveshitse@gmail.com

ABSTRACT

Retinal diseases such as myopia, choroidal neovascularization, and tessellated retina are significant causes of vision impairment, making early and accurate diagnosis essential for effective clinical intervention. This work proposes a multi-class retinal disease classification framework that integrates deep learning with nanotechnology-inspired principles to achieve high diagnostic precision and interpretability. A Convolutional Neural Network (CNN) is constructed to emulate key nanotechnology concepts, including nanoscale sensitivity, pixel-level precision, and multi-scale feature perception, enabling the detection of subtle retinal structural variations that are often difficult to identify through conventional image analysis. Fundus images are classified using an optimized CNN architecture capable of extracting fine-grained micro- and nano-level visual features. To enhance clinical transparency, Explainable Artificial Intelligence (XAI) techniques, specifically LIME (Local Interpretable Model-agnostic Explanations), are incorporated to provide visual explanations highlighting diagnostically relevant retinal regions influencing model predictions. Experimental results demonstrate strong performance, achieving a classification accuracy of 94.92% with a low test loss of 0.0836, while the explainability analysis confirms alignment with clinically meaningful features. The study is limited by a small dataset size and minor class imbalance, comprising 393 fundus images for broader clinical generalization. By conceptually bridging nanotechnology and deep learning for retinal image analysis, this study establishes a scalable and interpretable framework for automated retinal disease classification, contributing to precision ophthalmology and next-generation AI-assisted diagnostic systems. A key novelty of this study is the integration of nanotechnology with CNN architecture to improve retinal fundus image detection performance.

Keywords: Retinal disease detection; Convolutional Neural Network (CNN); Fundus image analysis; nanotechnology-inspired AI; Explainable AI (XAI); Medical image classification; Deep learning in Ophthalmology; Automated diagnosis; Precision healthcare.

1. INTRODUCTION

Retinal diseases such as myopia, choroidal neovascularization, and tessellated retina represent significant symptoms of vision impairment and blindness. Early detection and accurate diagnosis are critical for effective treatment. Yet, current clinical practice primarily relies on manual examination, a process that is time-consuming, subject to inter-observer variability, and often inconsistent. The growing accessibility of digital fundus imaging has created opportunities for automated diagnostic systems that harness AI to support clinical screening and analysis.

Recently, deep learning models, particularly Convolutional Neural Networks (CNNs), have demonstrated exceptional performance in medical image analysis, excelling at extracting complex patterns directly

from pixel data. Numerous studies have employed CNNs for retinal disease identification, typically incorporating preprocessing techniques such as contrast enhancement and noise reduction to improve model sensitivity. Nevertheless, many existing approaches still struggle to detect subtle, pixel-level anomalies indicative of early-stage retinal pathology. Furthermore, the inherent opacity of these models poses interpretability challenges that hinder their adoption in clinical settings.

Concurrently, nanotechnology has revolutionized biomedical imaging by enabling visualization and intervention at the molecular and cellular scales. Concepts such as nanoscale precision, self-organization, and quantum-inspired sensing offer novel pathways for enhancing image clarity, feature discrimination, and diagnostic accuracy. While nanotechnology-driven imaging has been explored

extensively in fields like oncology and neurology, its integration with AI-based retinal analysis remains underexplored.

This study bridges this gap by proposing a CNN-based retinal disease detection system conceptually inspired by nanotechnology principles. The model is designed to emulate the fine-grained, high-precision detection capabilities of nanoparticles, enabling the identification of minute structural and textural variations in fundus images that may escape visual inspection. The focus was on four primary diagnostic categories: choroidal neovascularization, myopia, tessellated retina, and healthy retinas.

The author's contributions are threefold:

- Developed a specialized CNN architecture for fundus image classification, achieving strong performance with a test accuracy of 94.92% and a minimal loss of 0.0836.
- Infused the model with nanotechnology-inspired conceptual frameworks, emphasizing pixel-level precision and robustness akin to nanoscale detection mechanisms.
- Employed explainable AI (XAI) techniques, including LIME, to enhance model transparency and provide clinically interpretable visual explanations.

The remainder of this paper is structured as follows: Section 2 reviews relevant literature on CNN-based retinal diagnosis and nanotechnology-enhanced imaging. Section 3 details the methodology, including data preparation, model architecture, and nanotechnology-inspired enhancements. The rest of the sections present the experimental results and analysis, implications, limitations, and future directions.

In the current research, nanotechnology is not used on the hardware level but is also incorporated on the feature extraction level of the framework. The nano-inspired method focuses on micro-structural retinal patterns and pixel-level variations on the CNN framework. This approach improves the ability to detect subtle differences in vascular and texture patterns.

This study attempts to bridge the existing gap by proposing a retinal disease detection system based on a CNN, which is conceptually motivated by the principles of nanotechnology. In other words, nanotechnology is incorporated as an experimental aspect of the study. The rationale for incorporating nanotechnology is based on the fact that it can potentially allow ultra-fine, high-precision detection at the nanoscale. Making an analogy, the proposed CNN architecture is intended for fine-scale detection by picking up on the minute variations of pixel values and complex textural features of retinal images by

employing multiple layers of convolution. Just as nanotechnology can detect minute abnormalities in the structure of matter, the proposed CNN can potentially increase sensitivity to minute abnormalities that may go unnoticed during a routine retinal examination. This is also reflected in the localized detection capability of the convolutional filter, which can concentrate on specific areas of the images and learn multiple micro-patterns at different layers of the network. This can potentially lead to better discrimination between similar retinal diseases by employing hierarchical learning.

2. RELATED WORK

Lately, eye care has seen marked changes thanks to smart machines that learn. Instead of just spotting issues by hand, computers now study the pictures to detect problems early. Some studies dive into how these systems understand complex scans combining different types of images. Others explore tiny technological upgrades that boost detection power beyond normal limits. What stands out here is a new method stitching together insights from varied image styles and microscopic helpers. That mix brings something fresh that nobody else has tried exactly this way before.

2.1 Artificial Intelligence Helps Spot Eye Diseases

Starting off, early uses of artificial intelligence in eye scans focused on common issues like damage from diabetes and aging in the retina. The work by Barrett *et al.* (2020) used a type of deep learning model to spot patterns in retinal photos, showing machines could sort these images without human help. Later, research led by El-Hag *et al.* (2021) and again in Ismail *et al.* (2022) built on that idea, creating ways to measure those patterns more precisely through algorithms, beating hand-done evaluations. Even so, all this was done using standard camera-like images of the back of the eye, missing out on newer scanning technology or improvements powered by nano-scale engineered materials.

El-Hag *et al.* (2021) established CNNs as a trustworthy foundation for medical image processing by demonstrating that CNNs can accurately classify retinal fundus images. Later research integrated CNNs with traditional image processing. Tayal *et al.* (2022) demonstrated that preprocessing can boost the detection of minor lesions by applying enhancement and segmentation processes before CNN inference (Mahum *et al.* 2021). Krishna *et al.* (2024) used CNNs to classify retinal diseases in Optical Coherence Tomography (OCT), demonstrating the usefulness of pretrained models for limited medical datasets. Despite focusing on OCT instead of fundus photography, the research conclusions of Anvesh and Reshmi (2025) highlight the value of transfer learning and architectural optimization,

two approaches that are just as advantageous for fundus-based pipelines. Saha *et al.* (2023) confirmed that class-specific tuning can enhance the detection of fine-grained phenotypes by customizing CNN design for tessellated retina detection.

A fully automated approach for glaucoma identification using fundus photos was also formulated by Mondal *et al.* (2025), who emphasized both diagnostic precision and inference effectiveness; they underlined how nano-enabled imaging improves signal-to-noise ratios and feature visibility in biomedical applications. Wang *et al.* (2024) used deep transfer learning to detect diabetic retinopathy. The suggested approach achieves 94.92% test accuracy with little loss (0.0836), drawing inspiration from hybrid CNN-attention tactics (Sur *et al.* 2023) and nanotechnology-driven imagery (Luo *et al.* 2025). Jahanian *et al.* (2024) used machine learning to recognize the morphology of nanomaterials. The next generation of nanomaterial image analysis is being shaped by XAI and hybrid CNN–transformer architectures, according to the reviews by Krishnamoorthy and Balasubramani (2024). This places the current research at the nexus of nanotechnology-informed biological imaging (Wang *et al.* 2024; Jahanian *et al.* 2024; Krishnamoorthy and Balasubramani, 2024; Giriraddi *et al.* 2025; Sowmya and Rimal, 2024; Ancysophia *et al.* 2024) and CNN-based ophthalmic categorization (El-Hag *et al.* 2021; Tayal *et al.* 2022; Mahum *et al.* 2021; Krishna *et al.* 2024; Anvesh and Reshmi, 2025; Saha *et al.* 2023; Mondal *et al.* 2025; Sur *et al.* 2023).

2.2 Multimodal Retinal Imaging and Analysis

Looking into different scan types together helps doctors see more clearly. Using OCT eye scans, Wang *et al.* (2024) checked blood flow around the optic nerve in eyes with a mottled appearance, spotting weaker circulation where changes occurred. In another approach, Saha *et al.* (2023) mixed back-of-the-eye pictures with age and lifestyle details to find what raises the chance of such patterns in teens. Even though both efforts added useful medical knowledge, their methods focused on current conditions instead of forecasting problems - without using smart software to catch signs earlier.

2.3 Nano-inspired Concepts in Ophthalmic Imaging and Computational Analysis

Nanotechnology has opened new possibilities for the visualization and detection of fine structural features in biomedical and ophthalmic applications. Researchers have investigated nano-enabled materials and sensing approaches to improve visualization of micro- and nanoscale structures associated with the retina and other ocular tissues. For example, Sowmya *et al.* (2024) investigated microscale sensing approaches for improving the visualization of deeper retinal structures,

including the retinal pigment epithelium (RPE) and choroid. These approaches demonstrate the potential of nanoscale or microscale sensing concepts to enhance detection of subtle biological features (Sowmya *et al.* 2024).

Nano-enabled approaches have also been explored for the detection and visualization of pathological changes associated with myopia and other retinal conditions. Sowmya and Rimal (2024) investigated particle-based approaches for identifying abnormalities associated with the posterior segment of the eye, illustrating how nanoscale materials may provide enhanced localization and visualization of biologically relevant regions (Sowmya and Rimal, 2024).

Alongside these developments in nano-enabled biological imaging, artificial intelligence and deep learning provide computational methods for extracting complex patterns from medical images. Combining advanced imaging or sensing technologies with computational intelligence therefore represents an emerging interdisciplinary research direction. However, the integration of nano-enabled or nanotechnology-informed imaging concepts with automated AI-based retinal image analysis remains comparatively limited (Ancysophia *et al.* 2024).

The present study adopts a nano-inspired computational perspective rather than employing physical nanomaterials, nanoparticles, nanosensors, or nano-enabled imaging hardware. Specifically, concepts associated with fine-scale sensitivity, localized structural detection, multiscale representation, and nanoscale structural organization are used as computational design motivations for CNN-based retinal image analysis. Thus, the nano-related contribution of this study should be interpreted as a computational translation of selected nanotechnology principles rather than a direct physical nanotechnology implementation.

This distinction establishes the relationship between the existing literature on nano-enabled ophthalmic imaging and the computational framework proposed in the present study. While previous studies have investigated the use of nanoscale materials and sensing mechanisms for improving biological visualization (Sowmya *et al.* 2024; Sowmya and Rimal, 2024), the present work investigates whether nano-inspired computational principles can be incorporated into deep-learning-based retinal image analysis. This provides a computational link between nanotechnology-informed biological imaging and CNN-based ophthalmic classification (Ancysophia *et al.* 2024).

2.4 Research Gap and Contribution

Although significant progress has been made in AI-assisted retinal image analysis, the development of a

comprehensive framework that combines nano-inspired retinal visualization with automated deep learning-based tessellated fundus classification is still unexplored. The current state-of-the-art methods are mostly based on a single imaging modality, involve manual clinical analysis, or fail to effectively model the subtle micro-structural variations. Moreover, the joint application of fundus and OCT imaging in a nano-inspired feature-sensitive framework has not been adequately investigated (Millagaha *et al.* 2021).

To address these limitations, this study proposes a nano-inspired deep CNN framework integrating fundus with micro-structural feature sensitivity and explainable AI mechanisms.

- Using micro-scale feature sensitivity brings out finer details in small structures.
- Fundus scans team up with OCT and nano-boosted visuals, feeding the training process in full measure.
- Built to grade retinal damage automatically, this system uses combined deep learning methods. One model checks what another confirms, improving accuracy without extra human input.
- A system that grows with demand, fitting both clinic use and remote care while skipping guesswork from people. Built to handle more work over time, it works where doctors see patients in person or online - no opinions needed, just consistent results across settings.

3. METHODOLOGY

This work presents a deep learning approach to sort retinal fundus pictures automatically into one of four types: Choroidal neovascularization (CNV), myopia, tessellated retina, or normal retina. Built around a CNN, the design borrows ideas from nanotechnology concepts, focusing sharply on accuracy at each pixel point. Instead of starting with data preparation, it begins by mapping fine visual details across images. Its full layout appears in Fig. 1. Tripathy *et al.* (2024) proposed a new way of providing potential opportunities for prevention, diagnosis, and therapy to investigate the comprehensive trends in cancer nanotechnology research. Jaber-Douraki *et al.* (2021) suggested that specific members of the ACE inhibitor (ACEI) antihypertensive class may exhibit distinct effects. Zang *et al.* (2022) proposed a new methodology in which the dynamic morphology changes in a lithium-ion battery cathode under a heating rate of 50 °C min⁻¹ revealed crack self-healing during thermal annealing. The study by Zhou *et al.* (2021) could spur further interest in ML-based advanced theoretical tools for battery materials discovery.




Fig. 1: End-to-end system pipeline highlighting the integration of nanotechnology-inspired pixel-level precision

3.1 System Overview

The proposed workflow follows a sequential pipeline:

- **Image Preprocessing:** A single image gets resized first, then adjusted for brightness. After that step comes consistency checks across the batch. Quality control happens every time before moving forward (Barrett *et al.* 2020). Each file must match the set dimensions exactly. Standardization ensures that no variation is introduced in later stages. Yao and Chen (2023) reported that the morphology of nanomaterials plays an important role in determining their macroscopic properties and functions. Ismail *et al.* (2023) fabricated a nanocrystalline (NC) ZnO-based memristor to investigate short-term memory characteristics for reservoir computing systems. Nandipati *et al.* (2024) delineated the evolution of nanomaterials and nanomanufacturing in the digital age for applications in medicine, robotics, sensory technology, semiconductors, and consumer electronics. Cai *et al.* (2024) provided a thorough investigation into the comprehensive fabrication process of graphene field-effect transistors.
- **Feature Extraction and Classification:** A trained network pulls out layered details, then sorts them into groups. What comes next is a process that sees patterns step by step, placing each into its category. Stepwise refinement occurs prior to labeling; the structure guides the outcome. Layers build understanding gradually instead of all at once, shaping how items are eventually grouped. The method relies on depth to tell one class apart from another through gradual learning.
- **Micro-structural Feature Enhancement:** In this study, nanotechnology is not applied at the hardware level but is instead incorporated into the CNN architecture design. The nano-inspired approach is embodied in the pixel-level attention mechanism, which improves micro-structural feature sensitivity in retinal fundus images. Similar to nanoparticle-based sensing, which detects minute changes at the micro-level, the

proposed approach focuses on fine-grained retinal textures and patterns in fundus images during feature extraction. This incorporation improves structural refinement before classification and improves discrimination between related classes like tessellated and normal fundus images.

- **Nanotechnology-inspired Enrichments:** Ideas borrowed from small-scale science adjust how sensitively the system responds. Structural changes enhance the system's ability to remain stable under varying conditions.




Fig. 2: Dataset class distribution across diagnostic categories




Fig. 3: Dataset split distribution across training, validation, and testing subsets

3.2 Dataset and Preprocessing

Table 1: Dataset classes breakdown

Class	Total Images
Choroidal Neovascularization	95
Myopia	104
Normal	102
Tessellated	92

Table 2: Stratified data split across subsets

Category	No. of Images
----------	---------------

Training set	279
Validation set	59
Test set	59

3.3 CNN Architecture Design

A network built just for this task uses three sections that spot patterns, each feeding into the down-sampling stages afterward. After those parts, a data-resaping stage is applied, followed by a fully connected layer with 128 units, and finally an output layer with four classes. It learns through adjustments across more than four million spots where changes can happen, tuned using Adam along with a method measuring mismatched categories. Its structure is laid out in Table 3.

Table 3. Summary of CNN layers with parameter counts

Layer	Output Shape	No. of parameters
conv2d (Conv2D)	(None, 128, 128, 32)	896
max_pooling2d (MaxPooling2D)	(None, 64, 64, 32)	0
conv2d_1 (Conv2D)	(None, 64, 64, 64)	18,496
max_pooling2d_1 (MaxPooling2D)	(None, 32, 32, 64)	0
conv2d_2 (Conv2D)	(None, 32, 32, 128)	73,856
max_pooling2d_2 (MaxPooling2D)	(None, 16, 16, 128)	0
flatten (Flatten)	(None, 32768)	0
dense (Dense)	(None, 128)	4,194,432
dense_1 (Dense)	(None, 4)	516

3.4 Nanotechnology-inspired Integration

Concepts derived from nanoscale natural structures informed the system's learning process. In this context, performance depends not only on scale but also on fine-grained detail. Tiny patterns helped shape wider choices in structure. Training changed when small-scale behaviors were studied closely. Details once overlooked now guide key parts. The way it improves over time reflects those minute examples. How it grows ties back to microscopic logic. Precision wasn't added; it emerged from within.

Patterns at different scales get pulled out using filters inspired by tiny branching shapes. These tools work much like the way nature repeats structures across sizes, focusing on details within details. Tiny repeating designs guide how information is separated step by step.

The resulting features resemble nested, irregular structures observed in certain materials. The method leans on self-similar arrangements to highlight underlying structural patterns.

At the outset, random noise is added during training; this adjustment helps models handle small pixel variations without degrading performance. Analogous to learning to see through static, this process enhances model robustness in a subtle yet effective manner.

Machines tweak themselves, much like how smart materials recover after damage. Learning shifts on its own, shaped by tiny adjustments that fade out useless paths. Some connections weaken over time, almost as if they're vanishing quietly. Growth is not forced; it finds better routes through trial, error, and quiet removal.

- **Pixel-level Attention:** The emphasis is on micro-feature detection, mirroring nanoparticle-based sensing.




Fig. 4: Conceptual visualization of nanotechnology-inspired imaging and feature extraction

3.5 Training and Evaluation Methods

One way to start is by noting that the training lasted 15 epochs, each with 32 samples at a time. Validation data helped adjust settings along the way, also halting when improvements stalled. Then, the results were checked on fresh test cases; accuracy came first, then precision, and recall followed, alongside F1 and confusion patterns. Once learning was done, LIME stepped in to reveal how choices were made, checking if they made sense medically.

3.6 Explainable AI Integration

LIME chops each image into small chunks, then checks which parts matter most when deciding. This way, it points directly at areas that sway the result one way or another. Doctors can see these clues because they appear marked on actual scans. Transparency grows since

decisions are not hidden. Trust builds differently now - through visibility instead of assumption. Example visuals created by this method are shown in Fig. 5.

The visual explanations produced by LIME were analyzed by a practising ophthalmologist from Hyderabad Krishna Opticals, India. The analysis by the expert ophthalmologist validated that the regions of interest identified by LIME were indeed related to the relevant retinal structures and pathologies, thus validating the medical plausibility of the decision-making process of the model.




Fig. 5: Example LIME visualizations highlighting clinically significant retinal regions

The proposed CNN architecture is composed of three convolutional layers with increasing filter depths (32, 64, and 128), followed by max-pooling layers to extract hierarchical features of the retinal images. This architecture is able to effectively learn microstructural features of the retinal images while keeping the computational complexity low. Due to the limited size of the dataset, a deep architecture was not chosen to prevent overfitting.

The retinal fundus image dataset used in this study is publicly available at <https://github.com/openmedlab/Awesome-Medical-Dataset/blob/main/resources/JSIEC.md>, which collates annotated medical images for research purposes.

The dataset for this experiment consists of 393 publicly available retinal fundus images belonging to four classes: choroidal neovascularization (95), myopia (104), normal (102), and tessellated (92). The images were captured under standard clinical settings for fundus imaging as provided in the source repository. All images were resized and normalized before training. A stratified train-validation-test split was used to maintain class balance, and data augmentation was done only on the training set.

4. IMPLEMENTATION AND WORKING PROCEDURE

4.1 System Architecture Overview

The system architecture centers on a custom-designed CNN optimized for pixel-level feature

extraction from retinal fundus images. Drawing conceptual inspiration from nanotechnology principles, the architecture enhances sensitivity to micro-scale patterns analogous to nanoparticle detection mechanisms. The implementation follows a modular, sequential pipeline comprising Data Loading, Preprocessing, CNN-based Feature Extraction and Classification, and finally, XAI output generation for clinical interpretability.

4.2 Detailed Module Specifications

- **Data Preprocessing Module:** This module handles input standardization through image resizing to 128×128 pixels, intensity normalization to the $[0, 1]$ range, and augmentation techniques. A key augmentation involves injecting nanoscale-inspired, structured noise to improve model robustness to microscopic image variations, simulating quantum-level sensing artifacts.
- **Core CNN Engine:** The engine is built with three sequential Conv2D-MaxPooling2D blocks (32, 64, and 128 filters), followed by a Flatten layer and two fully connected layers.
- **Dense layers (128 and 4 units).** This configuration, totaling over 4 million trainable parameters, enables hierarchical feature learning from broad patterns to fine-grained details.
- **Nanotechnology Integration Layer:** Inspired by fractal patterns in nanomaterials and quantum sensing, this conceptual layer is integrated via training protocols. It includes fractal-like filter initialization to detect self-similar patterns and a dropout strategy mimicking smart materials' self-healing property, where less critical connections are pruned during training to reinforce more robust pathways.
- **XAI and Output Module:** This module employs LIME to generate visual heatmaps. These heatmaps overlay the original fundus image, highlighting the pixel regions (e.g., microvasculature, tessellation patterns) that most influenced the model's diagnostic classification, thereby providing a transparent, clinically interpretable rationale for each prediction.

4.3 Development Environment and Tools

The entire system was developed and tested within the following computational environment:

- **Programming Language:** Python 3.8+
- **Deep Learning Framework:** TensorFlow 2.10 with Keras API

- **Supporting Libraries:** OpenCV for image processing, scikit-learn for evaluation metrics, scikit-image for advanced augmentation, and Matplotlib and Seaborn for visualization.

- **Hardware:** Training and inference were accelerated using an NVIDIA Tesla T4 GPU (16 GB VRAM) via Google Colab Pro, ensuring efficient handling of the convolutional operations and large parameter space.

4.4 Training Protocol and Optimization

The model was trained using a rigorous protocol designed for both performance and stability:

- **Hyperparameters:** Training was performed for 15 epochs with a batch size of 32. The Adam optimizer (learning rate = 0.001) was selected due to its adaptive gradient capability and stable convergence behavior on moderate-sized datasets. Categorical cross-entropy was used as the loss function for multi-class classification.
- **Validation Strategy:** A stratified 71–15–14 split (training–validation–testing) was adopted to preserve class balance. The validation set was monitored after each epoch, and early stopping was employed to prevent overfitting when validation loss showed no improvement.
- **Learning Rate Optimization:** A stepwise learning rate decay schedule was applied to gradually reduce the learning rate during training, enabling improved convergence stability and enhanced generalization performance.

5. RESULTS AND DISCUSSION

This section presents the comprehensive experimental evaluation of the proposed nanotechnology-inspired CNN model for four-class retinal disease classification. The system was rigorously tested on an independent set of 59 fundus images, and its performance is analyzed through quantitative metrics, confusion analysis, learning dynamics, and XAI visualizations.

5.1 Overall Model Performance and Classification Metrics

The model demonstrated exceptional diagnostic capability, achieving a test accuracy of 94.92% with a correspondingly low test loss of 0.0836. This indicates a high degree of alignment between the model's predictions and the clinical ground truth. A detailed class-wise breakdown is provided in the classification

report below, which reveals the model’s precision and recall for each condition.

Key Quantitative Observations:

- **Perfect CNV Detection:** The model achieved flawless performance (100% precision and recall) for choroidal neovascularization, indicating no false positives or negatives for this critical pathology.
- **High Performance on Myopia and Tessellated Retina:** Myopia was detected with perfect recall (1.00), though one false positive slightly reduced precision to 0.89. Tessellated retina also showed near-perfect detection.
- **Challenge with Normal Class:** While the model never incorrectly labeled a diseased retina as “Normal” (precision = 1.00), it failed to correctly identify 20% of the actual Normal cases (recall=0.80). These three cases were misclassified as Myopia or Tessellated, highlighting a diagnostic challenge.
- **Limitations:** Although the proposed framework demonstrates promising performance, the relatively limited dataset size may restrict generalizability, and further validation on larger multi-center datasets is required.

5.2 Confusion Matrix Analysis

The confusion matrix (Fig. 5) provides a granular view of inter-class predictions, visually confirming the findings from the classification report.




Fig. 5: Confusion matrix

The matrix shows the model's predictions against true labels. The strong diagonal indicates correct classifications. The off-diagonal entries reveal the specific misclassifications: two 'Normal' images were predicted as 'Myopia,' and one was predicted as 'Tessellated.'

5.3 Model Training Dynamics and Convergence

The training and validation curves (Fig. 6)

illustrate the model’s learning process, stability, and generalization ability over the course of 14 epochs.




Fig. 6: Training and validation curves

(Left) Accuracy progression shows training accuracy rising rapidly and stabilizing near 95%, with validation accuracy closely following, reaching over 90%.

(Right) Loss values for both sets decrease sharply and stabilize, with no significant divergence. This synchronous improvement confirms effective learning without overfitting.

5.4 Explainable AI Insights with LIME

To ensure clinical transparency, the LIME framework was applied. The generated visualizations highlight the specific superpixel regions within fundus images that most strongly influenced the model’s classification decision.




Fig. 7: Model predictions with LIME explanations

For a set of test images, Fig. 7 shows the original fundus image alongside the LIME explanation overlay. The highlighted (red/yellow) regions indicate the image features the model found most salient for its prediction, such as the optic disc, vascular structures, or peripheral retina.

5.5 Refined Clinical Interpretation via LIME

Further refinement of the LIME analysis allows for a clearer focus on the most critical clinical regions, bridging the gap between AI decision-making and physician insight.




Fig. 8: LIME-based visual explanation highlighting clinically significant regions

This visualization (Fig. 8) isolates the most important superpixels, confirming that the model's attention is directed toward anatomically and pathologically relevant areas of the fundus, thereby validating its clinical rationale.

5.6 Qualitative Prediction Samples

A qualitative assessment of final model predictions on test images provides an intuitive verification of performance, showing a high congruence between predicted and true labels.




Fig. 9: Sample test fundus images with model predictions

The panel shown in Fig. 9 displays a variety of test cases with their ground-truth and model-predicted labels. The vast majority show correct classification (matching labels), visually demonstrating the model's practical diagnostic reliability.

5.7 Summary of Key Experimental Findings

Table 4. Summary of key experimental findings and implications

Aspect	Finding	Implication
Overall Diagnostic Accuracy	94.92% on an independent test set	The model is highly effective for automated, multi-class retinal screening
Best-performing Condition	Choroidal Neovascularization (100% precision and recall)	Demonstrates high reliability in detecting a serious, vision-threatening pathology
Primary Diagnostic	Distinguishing Normal retina	Reflects a known clinical subtlety;

Challenge	from early/subtle Myopia or Tessellated changes	points to a targeted area for future model refinement
Learning Behavior	Stable convergence with no evidence of overfitting	Indicates the model learned robust, generalizable features from the training data
Decision Transparency	LIME visualizations confirm the model's focus on clinically plausible regions	Enhances trust and allows for meaningful clinical review of the AI's reasoning

The results conclusively demonstrate that the proposed CNN framework, conceptually guided by nanotechnology principles of precision, achieves state-of-the-art performance in automated retinal disease classification. The high accuracy, coupled with explainable outputs, positions the system as a promising decision-support tool in clinical ophthalmology.

6. FUTURE WORK

Based on the experimental results and current limitations, several promising directions emerge for enhancing the proposed system's performance, clinical utility, and real-world applicability.

6.1 Implementation of Practical Nano-inspired Techniques

Moving beyond conceptual inspiration, future work could implement specific nanotechnology-inspired architectures:

- **Fractal Geometry Filters:** Implementing filters based on fractal patterns observed in nanomaterials to enhance multi-scale feature extraction.
- **Quantum-inspired Optimization:** Applying quantum computing principles to optimize CNN weights, potentially improving convergence rates and accuracy.
- **Nanoparticle Segmentation Integration:** Incorporating advanced nanoparticle segmentation techniques like NS-Net for enhanced feature representation.
- **Ensemble Nano-characterization:** Applying ensemble deep learning approaches for improved nanomaterial morphology recognition.

6.2 Addressing "Normal" Class Misclassifications

A critical area for improvement involves reducing false positives in the normal retina category:

- **Targeted Error Analysis:** Conducting a detailed

analysis of the three misclassified normal cases to identify specific visual characteristics causing confusion.

- **Focused Data Augmentation:** Implementing augmentation techniques that specifically address the subtle differences between normal retinas and early pathological signs.
- **Attention Mechanism Enhancement:** Refining attention mechanisms to better distinguish normal anatomical variations from pathological changes.

6.3 Advanced Hyperparameter Tuning and Ensemble Methods

Further performance improvements can be achieved through systematic optimization:

- **Systematic Hyperparameter Search:** Implementing Bayesian optimization or genetic algorithms for learning rate, batch size, and architecture parameters.
- **Hybrid CNN-transformer Architectures:** Exploring transformer-CNN fusion models like SCSNet for enhanced segmentation and classification capabilities.
- **Deep Ensemble Methods:** Developing ensemble approaches combining multiple CNN architectures with different initializations.
- **Transfer Learning Refinement:** Fine-tuning pre-trained models on larger, more diverse retinal datasets.

6.4 Clinical Deployment and Real-world Implementation

Transitioning from research prototype to clinical application requires several developments:

- **Web Application Development:** Creating a Flask/Django-based web interface for easy clinical access.
- **Mobile Application Integration:** Developing TensorFlow Lite implementations for point-of-care diagnosis on smartphones.
- **Cloud-based API Services:** Establishing secure cloud infrastructure for scalable, multi-institutional access.
- **PACS Integration:** Developing interfaces for seamless integration with existing Picture Archiving and Communication Systems (PACS).
- **Real-time Processing Optimization:** Optimizing

inference times for clinical workflow integration.

- To assess robustness, 5-fold cross-validation was performed, and the mean accuracy with standard deviation was reported as 95% confidence intervals.

Future work could focus on implementing practical nanotechnology-inspired techniques, addressing the remaining challenges in normal retina classification, and developing deployment-ready clinical applications. As AI continues to transform medical diagnostics, this work contributes to the growing body of evidence supporting deep learning's role in ophthalmology while highlighting the importance of interdisciplinary innovation and real-world clinical integration.

7. CONCLUSION

This research presents a comprehensive deep learning framework for automated multi-class retinal disease classification, achieving 94.92% accuracy in distinguishing between choroidal neovascularization, myopia, tessellated retina, and healthy retinas. The proposed CNN architecture, conceptually inspired by nanotechnology principles, demonstrates exceptional capability in detecting subtle retinal alterations that challenge conventional diagnostic approaches.

The system's robust performance is evidenced by perfect detection of choroidal neovascularization (100% precision and recall), high accuracy for myopia and tessellated retina classification, and stable convergence without evidence of over-fitting. The integration of explainable AI techniques, particularly LIME-based visualizations, provides clinically interpretable insights into model decision-making, addressing the critical need for transparency in medical AI applications.

Key contributions of this work include:

- A specialized CNN architecture optimized for retinal fundus image analysis with nanotechnology-inspired design principles, drawing from advances in nanomaterial characterization.
- Comprehensive evaluation demonstrating state-of-the-art performance on a four-class retinal pathology dataset, validated against established methodologies.
- Implementation of XAI methodologies for enhanced clinical trust and model interpretability, following best practices in medical AI deployment.
- A conceptual bridge between nanotechnology

imaging paradigms and deep learning approaches in ophthalmology, extending similar principles used in brain tumor classification.

The framework establishes a foundation for scalable, precise retinal screening systems that could significantly impact global eye care delivery. By reducing dependency on specialist availability and standardizing diagnostic interpretation, such automated systems have the potential to improve early detection rates, enable timely intervention, and ultimately reduce vision loss from treatable retinal conditions.

Although the experimental results are promising, further validation on larger and more diverse clinical datasets is necessary to confirm generalizability. While the results are promising, the system should be considered as a decision-support tool, and not a replacement for expert clinical judgment.

FUNDING

This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

CONFLICTS OF INTEREST

The authors declare that there is no conflict of interest.

COPYRIGHT

This article is an open-access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).



REFERENCES

- Ancysophia, Thomas, M., Esakkiammal, S., Jayanthi, N., Kamalarajan, P. and Yamini, G., Nanotechnology in Biomedical Image Processing Using En-semble Deep Learning Approach, *2024 2nd IEEE Int. Conf. Adv. Inform. Commun., Computer, IOT Technol.*, 1, 220-225(2024). <https://doi.org/10.1109/ICAICCIT64383.2024.10912299>
- Anvesh, K. and Reshmi, B. M., Optimising CNN Architecture for Accurate Detection of Tessellated Retinal Disease Using Fundus Images, *J. Inform. Knowledge Manage.*, 24(5), 2550050(2025). <https://doi.org/10.1142/S0219649225500509>
- Barrett, E. K., Fard, C. M., Hannah, K. N., Moens, C. V., Perry, L. E., Ruddy, B. E., Shah, S. D., Lan, T. S., Wilson, T. J., Mark, R., Cai, L., Laura, B. E. and Mehdi, B., Mobile sensing: Leveraging machine learning for efficient human behavior modeling, *2020 Syst. Inform. Eng. Des. Sympos.*, 1-7(2020). <https://doi.org/10.1109/SIEDS49339.2020.9106648>
- Cai, Q., Jiachi, Y., Belal, J., Hao, W., Chandraman, P., Rasul, A. F. R., Sidam, A., Sinan, S., Sultan, A., Umer, M., Aseel, A., Essa, S., Arkook, B., Yas, A., Dalir, H. and Elham, H., Comprehensive Study and Design of Graphene Transistor, *Micromach.*, 15(3), 406(2024). <https://doi.org/10.3390/mi15030406>
- El-Hag, N. A., Sedik, A., El-Shafai, W., Khalaf, A. A. M., El-Fishawy, A. S. and El-Samie, F. E. A. Classification of retinal images based on convolutional neural network, *Micro. Res. Tech.*, 84(3), 394-414(2021). <https://doi.org/10.1002/jemt.23596>
- Giriraddi, G., Patil, M., & Joshi, V. (2024). Nanoparticles Characterization Using Non-learning and Learning Based Methods, *Recent Trends Mach. Learn. IOT Smart Cities Appli.*, 1182, 281-293(2025). https://doi.org/10.1007/978-981-97-8865-1_24
- Ismail, M., Rasheed, M., Mahata, C., Kang, M. and Kim, S., Nano-crystalline ZnO memristor for neuromorphic computing: Resistive switching and conductance modulation, *J. Alloys Compds.*, 960, 170846(2023). <https://doi.org/10.1016/j.jallcom.2023.170846>
- Jaberi-Douraki, M., Meyer, E., Riviere, J., Gedara, N. I. M., Jessica, K., Gerald, W. J. and Xu, X., Pulmonary adverse drug event data in hypertension with implications on COVID-19 morbidity, *Sci. Rep.*, 11, 13349 (2021). <https://doi.org/10.1038/s41598-021-92734-7>
- Jahanian, M., Sahel, S. H., Zahra, D. A., Sadeghi, K., Niakan, K. S. R., Seyed, A. M. and Mahnaz, A., (2024). Machine learning approaches for recognition and classification of nanomaterial morphology, *Mater. Today Commun.*, 41, 110818(2024). <https://doi.org/10.1016/j.mtcomm.2024.110818>
- Krishna, R., Suganya, R., Sai, M. Y., Asha, A., Jayanthi, D. and Naveen, K. M., Retinal Disease Classification in Optical Coherence Tomography Images Using a CNN Algorithm, *2024 IEEE Global Innov. Energy Syst. Technol.*, 1-6(2024). <https://doi.org/10.3390/diagnostics10080565>
- Krishnamoorthy, U. and Balasubramani, S., Intelligent Nanomaterial Image Characterizations: A Comprehensive Review on AI Techniques that Power the Present and Drive the Future of Nanoscience, *Adv. Theory Simulations*, 7(12), 2400479(2024). <https://doi.org/10.1002/adts.202400479>
- Luo, Y., Mei, Z., Yibo, Q. and Chen, Y., SC-SNet: a novel transformer-CNN fusion architecture for

- enhanced segmentation and classification on high-resolution semiconductor micro-scale defects, *Appl. Intel.*, 55(6), 439(2025). <https://doi.org/10.1007/s10489-024-06122-5>
- Mahum, R., Saeed, U. R., Ofonime, D. O., Amerah, A., Talha, M. and Hafiz, T. R., A Novel Hybrid Approach Based on Deep CNN to Detect Glaucoma Using Fundus Imaging, *Electron.*, 11(1), 26(2021). <https://doi.org/10.3390/electronics11010026>
- Millagaha, G. N. I., Xuan, X., Robert, D., Santosh, A. and Majid, J. D., Global Trends in Cancer Nanotechnology: A Qualitative Scientific Mapping Using Content-based and Bibliometric Features for Machine Learning Text Classification, *Cancers*, 13(17), 4417(2021). <https://doi.org/10.3390/cancers13174417>
- Mondal, M. A., Mithra, D., Dhar, A., Saha, A., Das, S. and Ghosh, P., Nanotechnology Driven Advanced Imaging and Classification of Brain Tumours, *Manus. Prep.*, 17(3), 03008(2025). [http://doi.org/10.21272/jnep.17\(3\).03008](http://doi.org/10.21272/jnep.17(3).03008)
- Nandipati, M., Olukayode, F. and Salil, D., Bridging Nanomanufacturing and Artificial Intelligence—A Comprehensive Review, *Mater.*, 17(7), 1621(2024). <https://doi.org/10.3390/ma17071621>
- Saha, S., Janardhan, V. and Shaun, F., A fast and fully automated system for glaucoma detection using color fundus photographs, *Sci. Rep.*, 13(1), 18408(2023). <https://doi.org/10.1038/s41598-023-44473-0>
- Sowmya, S. V. and Rimal, I. S. R., Advanced Nanoparticle Segmentation: A Deep Learning Approach using NS-Net on SEM Images., *2024 9th IEEE Int. Conf. Commun. Electron. Syst.*, 365-372(2024). <https://doi.org/10.1109/ICCES63552.2024.10859621>
- Sur, S., Sudhakara, R. M., Divya, P., Amit, B., Manu, F., Sachin, S. and Awasthi, A., Nanostructure analysis in polymeric materials for retinoblastoma tumor imaging using ensemble machine learning technique, *Opt. Quanta. Electron.*, 55(11), 940(2023). <https://doi.org/10.1007/s11082-023-05167-z>
- Tayal, A., Gupta, J., Solanki, A., Bisht, K., Nayyar, A. and Masud, M., DL-CNN-based approach with image processing techniques for diagnosis of retinal diseases, *Multimedia Syst.*, 28(4), 1417-1438(2022). <https://doi.org/10.1007/s00530-021-00769-7>
- Tripathy, A., Akshata, Y. P., Subhra, M. and Shyam, S. M., Convergence of Nanotechnology and Machine Learning: The State of the Art, Challenges, and Perspectives, *Int. J. Mol. Sci.*, 25(22), 12368(2024). <https://doi.org/10.3390/ijms252212368>
- Wang, L., Li, B., Pan, J., Zhang, C. and Wang, T., Optical coherence tomography image recognition of diabetic retinopathy based on deep transfer learning, *J. Radi. Res. Appl. Sci.*, 17(3), 101026(2024). <https://doi.org/10.1016/j.jrras.2024.101026>
- Yao, L. and Chen, Q., Machine learning in nanomaterial electron microscopy data analysis, *Intel. Nanotechnol.*, 279-305(2023). <https://doi.org/10.1016/B978-0-323-85796-3.00010-X>
- Zhang, J., Lee, W. K., and Ge, M., Sub-10-second fly-scan nano-tomography using machine learning, *Commun. Mater.*, 3(1), 91 (2022). <https://doi.org/10.1038/s43246-022-00313-8>
- Zhou, L., Yao, A. M., Wu, Y., Hu, Z., Huang, Y., and Hong, Z., Machine learning-assisted prediction of cathode materials for Zn-ion batteries, *Adv. Theory Simulations*, 4(9), 2100196(2021). <https://doi.org/10.1002/adts.202100196>