



## Review of the Synthesis of Nano-Sized Ash from Local Waste for Use as Admixture or Filler in Engineering Soil Stabilization and Concrete Production

K. C. Onyelowe<sup>1\*</sup>, F. O. Okafor<sup>2</sup>

<sup>1\*</sup>Department of Civil Engineering, Michael Okpara University of Agriculture, Umudike. P.M.B. 7267, Umuahia 440109, Abia State, Nigeria.

<sup>2</sup>Department of Civil Engineering, Faculty of Engineering, University of Nigeria, Nsukka, Nigeria.

Received: 25.10.2015 Accepted: 10.11.2015 Published: 30-12-2015

### Abstract

The synthesis of local nano-sized ash materials from local waste burnt and completely pulverized for use as admixtures or fillers in the stabilization or modification of weak engineering soil and the production of concrete is reviewed and the principles behind this all important aspect of nano technology X-rayed to give geotechnical engineers a clue and new turn in this area. These local waste materials as captured are palm bunch ash, coconut shell ash, palm kernel shell ash, bagasse ash, vehicle tyre ash, engine combustion ash, cigarette ash, fiber glass, pozzolan etc. Over the years, previous researches in the area of soil modification and stabilization of weak engineering soil have shown that remarkable improvement have been recorded in soil stabilization by using these ashes in their macro and micro scales. But in this era of nano technology and advent of nano-materials like nano copper, nano silica, nano carbon, nano aluminate, nano ferrite etc., resulting from chemical synthesis for various engineering uses, there is also the need to look into our readily available waste materials to nano-size the ashes making use of nano-sieves and nano filters and subjecting the collected powder to XRD test. These will lend to the research, parameters like wave length of X-ray ( $\lambda$ ), full width of half maximum ( $\beta$ ) and X-ray diffraction angle ( $\theta$ ). With these parameters, the average particle size of the powder under study would be determined using Debye-Scherrer's formula as shown in Equation 1 and establish the important fact that the powder belongs to nano-sized particle ranging between 0.1 to 999 nm as either 0-D, 1-D, 2-D or 3-D nanomaterial. In the same vein, the nano-sized particles are used as fillers in the production of concrete which is subjected to strength characteristic tests to establish the improvements on concrete properties. With this approach, local waste materials ash is used at the nano-scale to affect engineering soil for use and improve the strength properties of both soil and concrete.

**Keywords:** Admixture; Concrete Production; Filler; Nano-sized Ash; Soil Stabilization; Synthesis.

### 1. INTRODUCTION

This is a general overview of the possibilities in terms of available literature of characterizing and synthesizing nanosized ash from local waste materials mainly in the developing world for use as admixture or fillers in the stabilization or modification of weak engineering soil and the production of concrete in the field of Materials and Geotechnical Engineering (Norazlan *et al.* 2015; Zaid *et al.* 2014). Nanosized ash in this context is any fine particle of average size within the range of 0.1 and 999 nm whose reactive

surface area may have increased by 100% which took its nature and characterization from nano technology (Fan and Yongfeng, 2015). The idea of nanotechnology was first introduced in the 1959 by Richard Feynman in his lecture entitled "There's Plenty of Room at the Bottom" (Zaid and Mohd, 2013) a technology that made remarkable and swift progress years after. Technological improvements and advancements in this area of nanotechnology provided a state of the art approach to geotechnics which is being explored by this research. Common types of nanomaterials include nanotubes, dendrimers,

---

\*K. C. Onyelowe Tel. no: +2348039547350  
Email: konyelowe@mouau.edu.ng

quantum dots and fullerenes. Nanomaterials have applications in the field of nanotechnology and displays different physical and chemical characteristics from normal chemicals (i.e. silver nano, carbon nanotube, fullerene, photocatalyst, carbon nano, silica) ([www.google.com](http://www.google.com), 2015). The National Nanotechnology Institute, NNI had defined “nanotechnology” as the control, comprehension and reformation of material based on the hierarchy of nanometers to develop matter with essentially new uses and a new constitution (Zaid and Mohd, 2013; Mansoori et al. 2008; Juh, 2007; Li-Ming et al. 2011). Considering this definition, nanotechnology is a novel approach in all sciences. Such an approach can be applied in geotechnical engineering in two ways:

- (i) in studying the soil structure in nanometer scale to gain a better understanding of soil nature, as well as in studying the performance of soils with different nanostructures
- (ii) in conducting soil manipulation at the atomic or molecular scale, which is facilitated by the addition of nanoparticles as an external factor to soil. It is important to note at this point that nanomaterials are classified into the following geometric groups thus
  - (i) 0-D: with all the dimensions at the nanoscale
  - (ii) 1-D: with two dimensions at the nanoscale and one dimension at the macro scale
  - (iii) 2-D: with one dimension at the nanoscale and two dimensions at the macroscale and
  - (iv) 3-D: with no dimension at the nanoscale and all dimensions at the macroscale.

The second approach as recorded above is particularly the basis and aim of this research work to harness the available waste materials ash which in the past years researchers have used in their macro and micro scale to improve the geotechnical properties of engineering soil (Nirmala and Singaravadelan, 2014). There have been nano-silica, nano-ferrite, nano-copper, nano-zinc, nano-sulphite, nano-carbonate, nano-aluminate, nano-titanium, nano-silver, nano-gold, carbon black (Masaki and Eiji, 2006), nano-clay, nano-ceramics (Reenu et al. 2015) etc that have been used and these nano particles have considerably at differently degrees improved the construction properties of engineering soil and saved a lot of cost in engineering projects (Mansoori et al. 2008; Ershadi et al. 2011; Fan and Yongfeng, 2015; Bao et al. 2011).

## 2. MATERIALS & METHOD

Waste materials e.g. palm bunch, baggasse, waste paper, exhaust ash, cigarette ash, coconut shell, palm kernel shell, dry animal bone, quarry dust, vehicle tyre etc are collected, sun dried, burnt and completely pulverized to nanosize the ash by passing the collected powder through nano filters or sieves with sizes 10 nm, 20 nm, 50 nm, 100 nm, 200 nm, 500 nm and 800nm (Anitha and Haresh, 2014). The above nanosized ash is subjected to characterization by X-ray Diffraction Test to determine the following parameters; wave length of x-ray ( $\lambda$ ), full width of half maximum ( $\beta$ ) and X-ray diffraction angle ( $\theta$ ) (Satish et al. 2015). The above technique is approached in various forms and procedures giving varying degrees of accuracy and precision thus High-Resolution Transmission Electron Microscope (HRTEM), Photon Correlation Spectroscopy (PCS) which uses a Malvern Zetasizer Nano ZS laser particle, Dynamic Light Scattering (DLS), Scanning Electron Microscope (SEM), Transmission Electron Microscope (TEM), Small Angle X-ray Scattering (SAXS), Scanning Mobility Particle Sizer (SMPS), Energy Dispersive Spectroscopy (EDS), Selected Area Electron Diffraction (SAED), Atomic Force Microscopy (AFM), Convergent Beam Electron Diffraction (CBED) etc. The Debye-Scherrer’s formula is thereafter applied to determine the average particle size ( $D$ ) of the ash under study which many researchers have applied previously though on the synthesis of the known nanomaterials as listed above as follows; (Thomas, 2005; Daniele, 2013; Ashley, 2011; ESN, 2008; Neale et al. 2009; Laila et al. 2010; Ahmad et al. 2013; Justyna, 2013; Zaid and Mohd, 2011; Asama et al. 2013; Xiao et al. 2005; Chang-jun et al. 2010; Chien-I et al. 2008; Hall et al. 2000; Sovan et al. 2011; Fan and Yongfeng, 2015; Bao et al. 2011; Kalpana et al. 2009; Kannan, 2010; Tay et al. 2012; Anamika et al. 2011; Vorgelegt, 2013; Kavitha et al. 2015; Akbari et al. 2011; Jennifer, 2007; Kikuo and Wuled, 2004; Li-Ming et al. 2011).

$$D = \frac{0.9\lambda}{\beta \cos\theta} \quad (1)$$

$\beta$  is obtained from the corrected FWHM by convoluting Gaussian profile which models the specimen broadening  $\beta_r$  as follows; (Bao et al. 2011; Kalpana et al. 2009; Kannan, 2010; Tay et al. 2012; Anamika et al. 2011; Vorgelegt, 2013; Kavitha et al. 2015; Akbari et al. 2011; Jennifer, 2007; Kikuo and Wuled, 2004; Li-Ming et al. 2011);

$$\beta_r^2 = \beta_0^2 - \beta_i^2 \quad (2)$$

Where  $\beta_0$  is observed broadening and  $\beta_i$  is instrumental broadening.

### 3. EXPECTED RESULTS

Over the years, geotechnical engineering has recorded remarkable improvement in the geotechnical properties of engineering soil through the application and use of ash from different classes of waste materials as admixtures in the stabilization of the engineering soil for sub-grade and road base construction and general stabilization of engineering soils for different geotechnical engineering purposes. The above has been at the macro and micro scales (Mohammed, 2007; Osinubi, 2009; Ahawike and Stephen, 2009; Ekpo and Ihedioha, 2010; Agbo and Eze-Uzoamaka, 2010). The present work has reviewed the synthesis of local nanosized ash from the already known substances in use and the application of same as admixture and fillers. Brunauer-Emmett-Teller, BET Surface Area Analysis and Peak Broadening Analysis have shown in previous researches that the foregoing procedure increases the reactive surface area of the ash with cementing materials and the soil under investigation thereby yielding modified soil with considerably higher and improved geotechnical properties (Rafat and Mohammad, 2011). Previous researches have also shown that many local waste materials at the macro and micro scales have been used as fillers to produce light weight concrete and recorded remarkable improvements in the concrete engineering and construction properties which include consistency, workability, slump, compressive strength etc at different curing time periods (Osadebe *et al.* 2007). However the use of nanomaterials as fillers have been in use and the records are there of the considerable improvement this has shown in the production of concrete (Behfarnia and Keivan, 2013; Laila *et al.* 2010; Konstantin *et al.* 2006; Farag *et al.* 2014; Ali *et al.* 2011; Hesam *et al.* 2013; Maheswaran *et al.* 2013). With the above improvements, it is hopeful that the increase in surface area of these ash materials at the nanoscale will improve the reaction index between the admixture/filler, cement/binder and other aggregate materials for the production of improved concrete.

### 4. CONCLUSION

With the foregoing it is obvious that the synthesis of nanosized ash from local waste materials for use as admixture and filler in the stabilization of weak engineering soil and concrete production respectively will make a remarkable breakthrough in the field of geotechnical engineering by considerably and alternately improving the strength properties of

engineering soil and concrete and at the same time place nanotechnology on another recognizable platform by adding to its numerous records in different fields of science and technology.

### FUNDING

This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

### CONFLICTS OF INTEREST

The authors declare that there is no conflict of interest.

### COPYRIGHT

This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC-BY) license (<http://creativecommons.org/licenses/by/4.0/>).



### REFERENCES

- Agbo, D. and Eze-Uzoamaka, O. J., Suitability of quarry-dust as improvement to cement stabilized laterite for road bases, *Electron. J. Geotech. Eng.*, 15(K), 1053-1066(2010).
- Ahawike, J. and Stephen, C., The effect of bagasse ash on the properties of cement stabilized oboro lateritic soil, Unpublished Project Work Submitted to Department of Civil Engineering, Michael Okpara University of Agriculture Umudike(2009).
- Ahmad, K. D., Yaser, K. and Ehsan, T., Synthesis of nano-alumina powder from impure kaolin and its application for arsenite removal from aqueous solution, *J. Environ. Health Sci. Eng.*, 11(1), 19(2013).  
[doi:10.1186/2052-336X-11-19](https://doi.org/10.1186/2052-336X-11-19)
- Akbari, B., Tavandashti, P. M. and Zandrahimi, M., Particle size characterization of nanoparticles – A practical approach, *Iran. J. Mater. Sci. Eng.*, 8(2), 48-56(2011).
- Ali Nazari, Mohammad Hossein Rafieipour and Shadi Riahi, The effects of CuO nanoparticles on properties of self compacting concrete with GGBFS as binder, *Mat. Res.*, 14(3), 307-316, (2011).  
[doi:10.1590/S1516-14392011005000061](https://doi.org/10.1590/S1516-14392011005000061)

- Anamika Mubayi, Sanjukta Chatterji, Prashant M. Rai and Geeta Watal, Evidence based green synthesis of nanoparticles, *Adv. Mat. Lett.*, 3(6), 519-525(2012). doi:10.5185/amlett.2012.icnano.353
- Anitha, P. and Haresh M. Pandya, Comprehensive Review of preparation methodologies of nano hydroxyapatite, *J. Environ. Nanotechnol.*, 3(1), 101-121(2014). doi:10.13074/jent.2013.12.132058
- Asama, N. N., Azhar, S. N. and Abdulla, M. S., Preparation and characterization of SnO<sub>2</sub> nanoparticles, *Int. J. Innov. Res. Sci. Eng. Technol.*, 2(12), 7068-7072(2013).
- Bao Ying, Zhan Liang, Wang Chunxiao, Wang Yanli, Yang Guangzhi, Yang Junhe, Qiao Wenming and Ling Licheng, Synthesis of carbon nanofiber/carbon foam composite for catalyst support in gas phase catalytic reactions, *New Carbon Mater.*, 26(5), 341-346(2011). doi:10.1016/S1872-5805(11)60086-3
- Behfarnia, K. and Keivan, A., The Effects of TiO<sub>2</sub> and ZnO nanoparticles on physical and mechanical properties of normal concrete, *Asian J. Civ. Eng. (BHRC)*, 14(4), 517-531(2013).
- Chang-jun Liu, Uwe Burghaus, Flemming Besenbacher and Zhong Lin Wang, Preparation and characterization of nanomaterials for sustainable energy production, *ACS Nano.*, 4(10), 5517-5526(2010). doi:10.1021/nn102420c
- Chien-I. W., Jiann-Wen, H., Ya-Lan, W., Shaw-Bing, W., Yun-Hwei, S and Mou-Yung, Y., Preparation of TiO<sub>2</sub> nanoparticles by supercritical carbon dioxide, *Mater. Lett.*, 62, 1923-1926(2008). doi.org/10.1016/j.matlet.2007.10.043
- Daniele, V., Taglieri, G, Gregori, A. and Volpe, R., New nano-cementing materials, The new boundaries of structural concrete session C - New Scenarios for Concrete, Dipartimento di Chimica, Ingegneria Chimica e Materiali, University of L'Aquila, Italy(2013).
- Ekpo, A. D. and Ihedioha, N. A., The Use of Bagasse Ash as Admixture in Cement Stabilized Oboro Lateritic Soil, Unpublished Project Work Submitted to Department of Civil Engineering, Michael Okpara University of Agriculture, Umudike, Nigeria, (2010).
- Ershadi, V., Ebadi, T., Rabani, A. R., Ershadi, L. and Soltanian, H., The effect of nanosilica on cement matrix permeability in oil well to decrease the pollution of receptive environment, *Int. J. Environ. Sci. Dev.*, 2(2), 128-132(2011). doi:10.7763/ijesd.2011.v2.109
- European strategy for nanosafety, Safe production and use of nanomaterials, *Nanosafe*, 4-7(2008).
- Fan Yang and Yongfeng Li, Synthesis and application of nanocarbon materials using plasma technology, *Int. J. Chem. Eng. Appl.*, 6(1), 49-52(2015). doi:10.7763/ijcea.2015.v6.449
- Farag Khodary, Abdel-sadek, M. S. and El-Sheshtawy, H. S., Mechanical properties of modified asphalt concrete mixtures using Ca(OH)<sub>2</sub> nanoparticles, *Int. J. Civ. Eng. Technol.*, 5(5), 61-68(2014).
- Hall, B. D., Zanchet, D. and Ugarte, D., Estimating nanoparticle size from diffraction measurements, *J. Appl. Cryst.*, 33, 1335-1341(2000). doi:10.1107/S0021889800010888
- Hesam Madani, Alireza Bagheri, Tayebeh Parhizkar, Amirmaziar Raisghasemi and Aliakbar Ramezani-poor, The aggregation status of nanosilicas and silica fume, used in cementitious mixtures, 3<sup>rd</sup> International Conference on Sustainable Construction Materials and Technologies, New York(2013).
- Jennifer Ann Dahl, Synthesis of functional nanomaterials within a green chemistry context, Unpublished PhD dissertation, Department of Chemistry, University of Oregon(2007).
- Juh, T. L., Physical properties of nanomaterials, *Encyclopedia of Nanoscience and Nanotechnology.*, X, 1-46(2007).
- Justyna, S., Synthesis of silver and gold nanoparticles using methods of green chemistry, *CHEMIK*, 67(10), 842-847(2013).
- Kalpna Awasthi, Rajesh Kumar, Himanshu Raghubanshi, Seema Awasthi, Ratnesh Pandey, Devinder Singh, Yadav, T.P and Srivastava, O. N., Synthesis of nano-carbon (nanotubes, nanofibres, graphene) materials, *Bull. Mater. Sci.*, 34(4), 607-614(2009). doi.org/10.1007/s12034-011-0170-9
- Kannan, M., Preparation and characterization of nano clay-filled polymer blends, *Plastics Research Online*, (2010). doi:10.1002/spepro.003051.
- Kavitha, S., Geetha, D. and Ramesh, P. S., Synthesis and characterizations of silver colloid nanoparticles stabilized by dextran, *J. Environ. Nanotechnol.*, 4(1), 50-55(2015). doi:10.13074/jent.2015.03.144139
- Kikuo Okuyama and Wuled Lenggoro, Nanoparticle preparation and its application - A Nanotechnology particle project in Japan, Proceedings of the 2004 International Conference on MEMS, NANO and Smart Systems (ICMENS'04) (2004).



- Konstantin Sobolev, Ismael Flores, Roman Hermosillo and Leticia M. Torres-Martínez, Nanomaterials and Nanotechnology for High-Performance Cement Composites, Proceedings of ACI Session on “Nanotechnology of Concrete: Recent Developments and Future Perspectives” November 7, 2006, Denver, USA.
- Laila Raki, James Beaudoin, Rouhollah Alizadeh, Jon Makar and Taijiro Sato, Review of cement and concrete nanoscience and nanotechnology, *Mater.*, 3, 918-942(2010); doi:10.3390/ma3020918
- Li-Ming Zhao, Lu-E Shi, Zhi-Liang Zhang, Jian-Min Chen, Dong-Dong Shi, Jie Yang and Zhen-Xing Tang, Preparation and application of chitosan nanoparticles and nano-fibers, *Braz. J. Chem. Eng.*, 28(3), 353-362(2011).
- Maheswaran, S., Bhuvaneshwari, B., Palani, G. S., Nagesh, R. I. and Kalaiselvam, S., An overview on the influence of nano silica in concrete and a research initiative, *Res. J. Rec. Sci.*, 2, 17-24(2012).
- Mansoori, G. A., Bastami, T. R., Ahmadpour, A. and Eshaghi, Z., Environmental Application of Nanotechnology, *Annual Review of Nano Research*, 2(2), 1-73(2008).
- Masaki Ozawa and Eiji Ōsawa, Carbon blacks as the source materials for carbon nanotechnology, *Carbon Nanotechnol.*, 6, 127-151(2006). doi:10.1016/b978-044451855-2/50009-7
- Mohammed, A. M., Evaluation of plasticity and particle size distribution characteristics of bagasse ash on cement treated lateritic soil, *Leonardo J. Sci.*, 10, 137-152(2007).
- Neale Jackson, Andreas Lopata, Terry Elms and Paul Wright, Engineered Nanomaterials: Evidence on the effectiveness of workplace controls to prevent exposure, Commonwealth of Australia(2009).
- Nirmala, R. and Singaravadelan, R., Comparative study on strength and permeability of cement mortar using micro and nano particles, *Int. J. Civ. Struct. Eng.*, 1(3), 69-82(2014).
- Norazlan Khalid, Mohd Fadzil Arshad, Mazidah Mukri, Kamaruzzaman Mohamad and Faizah Kamarudin, Influence of nano-soil particles in soft soil stabilization, *Electron. J. Geotech. Eng.*, 20(2), 731-738(2015).
- Osadebe, N. N., Mbajorgu, C. C. and Nwakonobi, N. N., An optimization model development for laterized concrete mix proportioning in building construction, *Nigerian Journal of Technology*, 26(1), 37-46(2007).
- Osinubi, K. J., Bafyau, V. and Eberemu, A. O., Bagasse ash stabilization of lateritic soil, *Springer Link Sciences and Business Media*, 271-280(2009). doi:10.1007/978-1-4020-9139-1\_26
- Rafat, S. and Mohammad, I. K., Supplementary Cementing Materials, ebook, *Springer*, New York(2011).
- Reenu Jacob, Nair, H. G. and Isac, J., Structural and morphological studies of nano-crystalline ceramic BaSr<sub>0.9</sub>Fe<sub>0.1</sub>TiO<sub>4</sub>, *Int. Lett. Chem. Phy. Astr.*, 41, 100-117(2014). doi:10.18052/www.scipress.com/ILCPA.41.100
- Satish Bykkam, Mohsen Ahmadipour, Sowmya Narisngam, Venkateswara Rao Kalagadda and Shilpa Chakra Chidurala, Extensive studies on X-Ray diffraction of green synthesized silver nanoparticles, *Adv. Nanoparticles*, 4(1), 1-10(2015). doi: 10.4236/anp.2015.41001
- Sovan Lal Pal, Utpal Jana, Manna, P. K., Mohanta, G. P. and Manavalan, R., Nanoparticle: An overview of preparation and characterization, *J. Appl. Pharma. Sci.*, 1(6), 228-234(2011).
- Tay Shiau Fong, Mohd Rafie Johan and Roslina Binti Ahmad, Synthesis and Characterization of Gold-Titanium-Mesoporous Silica Nanomaterials, *Int. J. Electrochem. Sci.*, 7, 4716 - 4726(2012).
- Thomas Abraham., Nanotechnology and Nanomaterials: Types, current/emerging applications and global markets, *Innovative Research and Products, Inc.*,(2005).
- Vorgelegt Von, Traceable determination of the size of nanoparticles using small-angle X-ray scattering, tag der wissenschaftlichen Aussprache, Berlin, Unpublished project(2013).
- Xiao, Y., Cai, Z., Wang, Z. L., Lai, B. and Chu, Y. S., An X-ray nano diffraction technique for structural characterization of individual nanomaterials, *J. Synchrotron Rad.*, 12, 124-128(2005). doi:10.1107/S0909049504028596
- Zaid, H. M. and Mohd, R. T., Effect of nanomaterial treatment on geotechnical properties of a penang soft soil, *J. Asian Sci. Res.*, 2(11), 587-592(2011).
- Zaid Hameed Majeed, Mohd Raihan Taha and Ibtehaj Taha Jawad, Stabilization of soft soil using nanomaterials, *Res. J. Appl. Sci. Eng. Technol.*, 8(4), 503-509(2014).
- Zaid, H. M. and Mohd, R. T., A Review of stabilization of soils by using nanomaterials, *Aust. J. Basic & Appl. Sci.*, 7(2), 576-581(2013).